

Special Issue on

Biochemistry of Mitochondrial Quality Control

Edited by:

Jeremy W Chambers

Assistant Professor, Department of Cellular Biology and Pharmacology, Florida International University, USA

Review Article

Enhanced Cell Mitochondrial Activity using Electrospun Nanofibers

Valencia Jacobs^{1,2,3,4*}

¹CSIR Materials Science and Manufacturing, Polymers & Composites, South Africa

²Department of Chemistry, Nelson Mandela Metropolitan University, South Africa

³UNESCO-UNISA AFRICA Chair in Nanosciences/Nanotechnology, University of South Africa, South Africa

⁴Nanosciences African Network, iThemba LABS-National Research Foundation, South Africa

*Corresponding author

Valencia Jacobs, CSIR Materials Science and Manufacturing, Polymers & Composites, P.O. Box 1124, Port Elizabeth 6000, South Africa, Tel: 27-041-508 3229; Fax: 27-0-41 583 2325; Email: vjacobs@csir.co.za

Submitted: 11 December 2014

Accepted: 16 June 2015

Published: 18 June 2015

ISSN: 2333-7109

Copyright

© 2015 Jacobs

OPEN ACCESS

Keywords

- Cell activity
- Electrospinning
- Biomaterials
- Tissue engineering

Abstract

Research in tissue engineering related to the improved processes using nanofiber scaffolds has seen considerable progress in the last decade in the regeneration and construction of a number of artificial tissue types. These designs are generally viewed from the perspective of possible sources for clinical implant and transplant materials. Nowadays, advancement in engineering of tissues often referred to as three-dimensional (3D) cell culture provides enhanced activities owing to the 3D systems that readily imitate the in vivo setting for differentiated organs, than a typical 2D cell culture. Electro-spinning has been useful in producing nanofibrous scaffolds with large surface area and high pore volume that has the potential to mimic the morphology of a tissue extracellular matrix and hence promoting cell attachment, proliferation and differentiation. This review reports improved processes of tissue revitalization utilizing electrospun nanofibrous scaffolds. Different tissue engineering approaches including their advantages have been discussed. Also, various biomaterials from both synthetic and natural origin have been elaborated.

ABBREVIATIONS

PCL: Polycaprolactone; PLA: Polylactic Acid; PHB: Polyhydroxybutyrate; ECM: Extracellular Matrix

INTRODUCTION

It is becoming apparent that biomaterials have a critical role to

play in the development and evolution of regenerative medicine. Tissue engineering is one interdisciplinary area that combines the principles of engineering and life sciences to advance biological substances that restore, maintain and revitalize the damaged tissues and organs [1-3]. To replace diseased, defected, or lost cartilage tissue and to restore natural tissue functions during regeneration process, biomaterial and biomechanical

considerations should be incorporated into a designed [4]. In the past, a large focus was on the development of biomaterials scaffolds for permanent tissue replacement. Among the few polyesters onto which human cells can either differentiate, divide or both, biocompatible and biodegradable PCL, PLA and PHB have been successfully electro spun into nanofiber scaffolds [1]. However, electrospun nanofibrous scaffolds are of great interest in tissue engineering due to their interconnected pores, their high surface area to volume ratio and architectural similarity to the native ECM [4]. These properties enable electrospun scaffolds to stimulate cell mitochondrial activities including cell adhesion, proliferation and differentiation but also improve spatial organization on the mesoscopic scale [1,5-9].

Tissue engineering approaches

Generally, engineered tissue is normally composed of primary or immortalized cells that are organized and cultured on the surface or inside a three-dimensional (3D) scaffold composed of either extracellular matrix proteins or analogous biomaterials [10]. However, utilizing regenerated tissue in biomedical research is to bridge the gap between traditional two-dimensional (2D) cell culture and the *in vivo* setting, thus, creating an environment that more closely represents the complex 3D structure of intrinsic tissue. In this tactic, the *in vitro* phenotype of cells in a 3D model, surrounded by extracellular matrix and other cells offers the ability to measure phenotypes that cannot be measured in 2D cell cultures and therefore in some cases will be more relevant to the *in vivo* situation [11,12]. Another powerful advantage of 3D systems is to apply a high-throughput method to perform phenotypic measurement of traits typically limited to organ systems in analogous to 2D culture models. Furthermore, electro spinning has proven to be one of the significant methods for fiber-based 3D scaffold production [13].

Electrospun Nanofibrous Scaffolds

Polymeric biomaterials and their blends have been widely utilized in biomaterials research due to their biodegradability. PCL, a hydrophobic polymer, is a well-known biocompatible polymer that has been successfully fabricated via electrospinning technology [14-16]. Electrospun PCL blends include natural biopolymers such as gelatin, chitosan and lecithin. However, PCL-gelatin blend can improve cell and neurite growth whereas PCL-chitosan blend promotes cell growth and expansion [17].

DISCUSSION AND CONCLUSIONS

The presence of high porous networks and large surface area in the morphology of Electrospun nanofibrous scaffolds can promote cell regeneration, proliferation and differentiation. Various approaches for tissue regeneration using a 3D *in vitro* model surrounded by extracellular matrix offers the ability to measure phenotypes that cannot be measured in 2D cell cultures.

REFERENCES

1. Daranarong D, Chan RT, Wanandy NS, Molloy R, Punyodom W, Foster

- LJ. Electrospun polyhydroxybutyrate and poly (L-lactide-co- ϵ -caprolactone) composites as nanofibrous scaffolds. *Biomed Res Int*. 2014; 2014: 741408.
2. Atala A, Mooney DJ. *Synthetic Biodegradable Polymer Scaffolds*, Birkhauser, Boston, Mass, USA. 1997.
3. Shalak R, Fox CF. Preface, in *Tissue Engineering*. Tissue Engineering, Liss, New York, NY, USA. 1988.
4. Jeong SI, Jeon O, Krebs MD, Hill MC, Alsberg E. Biodegradable photo-crosslinked alginate nanofibre scaffolds with tuneable physical properties, cell adhesivity and growth factor release. *Eur Cell Mater*. 2012; 24: 331-343.
5. Feng S, Shen X, Fu Z, Shao M. Preparation and Characterization of Gelatin-Poly (L-lactic) Acid/Poly (hydroxybutyrate-co-hydroxyvalerate) Composite. *Nanofibrous Scaffolds, J MacromolSci Part B: Physics*. 2011; 50: 1705-1713.
6. Mooney DJ, Langer RS. *The Biomedical Engineering Handbook*, edited by Bronzino JD, CRC Press. 1995.
7. Shih YR, Chen CN, Tsai SW, Wang YJ, Lee OK. Growth of mesenchymal stem cells on electrospun type I collagen nanofibers. *Stem Cells*. 2006; 24: 2391-2397.
8. Prabhakaran MP, Venugopal J, Chan CK, Ramakrishna S. Surface modified electrospun nanofibrous scaffolds for nerve tissue engineering. *Nanotechnology*. 2008; 19.
9. Venugopal J, Low S, Choon AT, Kumar AB, Ramakrishna S. Electrospun-modified nanofibrous scaffolds for the mineralization of osteoblast cells. *J Biomed Mater Res A*. 2008; 85: 408-417.
10. Petersen MC, Lazar J, Jacob HJ, Wakatsuki T. Tissue engineering: a new frontier in physiological genomics. *Physiol Genomics*. 2007; 32: 28-32.
11. Asnes CF, Marquez JP, Elson EL, Wakatsuki T. Reconstitution of the Frank-Starling mechanism in engineered heart tissues. *Biophys J*. 2006; 91: 1800-1810.
12. Liu H, Fan H, Cui Y, Chen Y, Yao K, Goh JC. Effects of the controlled-released basic fibroblast growth factor from chitosan-gelatin microspheres on human fibroblasts cultured on a chitosan-gelatin scaffold. *Biomacromolecules*. 2007; 8: 1446-1455.
13. Wolun-Cholewa M, Langer K, Szymanowski K, Glodek A, Jankowska A, Warchol W, et al. An efficient 3D cell culture method on biomimetic nanostructured grids. *PLoS One*. 2013; 8: 72936.
14. Santos Jr AR. *Bioresorbable polymers for tissue engineering*. Tissue Engineering, Eberli D (Ed.), ISBN: 978-953-307-079-7.
15. Törmälä P, Pohjonen T, Rokkanen P. Bioabsorbable polymers: materials technology and surgical applications. *Proc Inst Mech Eng H*. 1998; 212: 101-111.
16. Barbanti SH, Zavaglia CAC, Duek EAR. Polímeros bioreabsorvíveis: engenharia de tecidos. *Polímeros: Ciência e Tecnologia*. 2005; 15: 13-21.
17. Sell SA, Wolfe PS, Garg K, McCool JM, Rodriguez IA, Bowlin GL. The use of natural polymers in tissue engineering: a focus on electrospun extracellular matrix analogues. *Polymers*. 2010; 2: 522-553.

Cite this article

Jacobs V (2015) Enhanced Cell Mitochondrial Activity using Electrospun Nanofibers. *JSM Biochem Mol Biol* 3(1): 1012.